



Model	Article number	Rope Ø		D Ø mm	Dm Ø mm	Drive group FEM	Max. tensile load kg at deflection		D1 Ø mm	L mm	C mm	H mm	B mm	E mm	S mm	K mm	M/M1 Ø mm
		Manual winch mm	Electric winch mm				90 deg	180 deg									
DSRB S 145/5	033447104	5	5	145	125	4m	1100	800	25	200	160	224	125	88	6	110	11.5/13
DSRB S 145/6	033447105	6	6	145	125	2m	1100	800	25	200	160	224	125	88	6	110	11.5/13
DSRB S 145/7	033447106	7	7	145	126	1Am	1100	800	25	200	160	224	125	88	6	110	11.5/13
DSRB S 185/8	033447107	8	8	185	160	2m	2300	1630	30	245	195	273	138	106	8	135	13.5/15
DSRB S 185/9	033447108	9	9	185	162	1Am	2300	1630	30	245	195	273	138	106	8	135	13.5/15
DSRB S 270/12	033447111	9-12	12	270	246	2m	2500	1800	40	360	290	407	191	138	10	202	18/20
DSRB S 325/14	033447117	14	14	325	297	2m	4500	3200	50	440	350	490	260	180	12	242	22/25
DSRB S 400/16	033447113	13-16	16	400	368	3m	5000	3800	50	530	430	612	302	212	15	310	26/30
DSRB S 400/18	033447114	18	18	400	364	2m	5000	3800	50	530	430	612	302	212	15	310	26/30
DSRB S 490/20	033447115	20	20	490	450	3m	8000	6000	65	650	580	694	313	220	16	340	34/40