

VANTAGE 5:1 Locking Casualty Pulley - 5m

P101

For transferring a casualty onto a rescue system without cutting connections

Strong, light, tangle free method of lifting a casualty onto a rescue system.

Extremely simple and intuitive to operate.

Features:

- 5:1 mechanical advantage
- Cut resistant sheath
- Cam locks automatically
- 8mm cord

Approved as PPE

5:1 if rigged to advantage (tail end attached at the load being lifted).

Special sheath material is flexible yet highly compressible. Prevents tangling and provides cut/abrasion resistance.

All components are approved as PPE. Functions as a secure single attachment so there is no need for an additional 'rated' connection.

Automatic locking allows efficient progress capture during rescue. The cam does not lock open, removing the risk of accidentally releasing the load.

8mm cord gives good grip for hauling.

Lengths available: 1.5m, 5m.

1.5m length allows full arms length reach without excessive slack.



Specifications:

NB: specifications and colour may change without notice.

Size: 5m max.

EN Test Mass: 140kg

Loading: 140kg SWL. 1.4kN WLL

Conformity: EN567:2013, EN12278:2007, EN564:2014

Materials: Anodised Aluminium Alloy, Stainless Steel, Nylon

Weight (kg):

Industries: All industries who work at height.