

FELCO C7 WIRE ROPE CUTTER

- Gives a clean cut without squashing thanks to the triangular cutting system
- Blades and centre bolt in high-quality hardened steel for exceptional performance
- Thumb catch designed for one-handed operation
- Pressed steel handles with non-slip grips



An outstandingly powerful tool for cutting steel wire rope. The C7 has a unique triangular jaws that never leaves a frayed cut. The C7 features hardened steel blades and center bolt. It cuts wire rope up to 1/4 inch or 7 mm thick, high tensile steel strands up to 5 mm thick, stainless steel strands up to 4 mm, extra tough wire rope or stands up to 3 mm. In addition, the C7 cuts electric cables of copper, aluminum or steel-cored aluminum up to 7 mm, aluminum or copper rods up to 5 mm diameter, steel rods up to 4 mm and tempered steel spring wire up to 2 mm.

Length 190,5 mm. Weight ca 290 grams.

CUTTING CAPACITIES

MATERIAL	MAXIMUM CUTTING DIAMETER
Galvanized steel wire rope, fibre core	7mm (0.28in)
Galvanized steel wire rope, steel core	6mm (0.24in)
Hard steel wire rope, resistance 160 kg/mm ²	5mm (0.2in)
Non-oxidable steel wire rope, resistance 190 kg/mm ²	4mm (0.16in)
Extra tough wire rope and strands, resistance 210 kg/mm ²	3mm (0.12in)
Electric cables (copper or aluminium) with steel core)	7mm (0.28in)
Aluminum- or copper rods	5mm (0.2in)
Iron rods, resistance 60 kg/mm ²	4mm (0.16in)
Tempered spring wire	2.5mm (0.1in)
Welded wire mesh	X
Rubber conveyor belt	X