

TENSOR Twin Energy Absorbing Lanyards
L02XXX
High specification EA lanyards with optional connectors
Features:

- High load rating, approved for users up to 140kg
- Durable protective cover
- High twist ropes
- Unique serial ID number

Available with a selection of connectors.

Heatshrink absorber with replaceable cover, tamper evident but with increased durability.

Absorber will not deploy at force less than 200kg. Min. strength 1500kg after deployment.

Patented ropes allow high degree of twist in lanyard legs, minimising kinking.

Unique serial ID number allows easy management of equipment.

Approved for users up to 140kg.

Code	Legs	Harness Connector	Length ***cm	Anchorage Connector
L02M***S	2	Oval	100/125/150	Scaff hook

*** Denotes length

NB: Weight dependent on option chosen.


Specifications:

NB: specifications and colour may change without notice.

Size:	100cm, 125cm or 150cm
EN Test Mass:	100kg
Loading:	Additionally tested 140kg Fall factor 2
Conformity:	EN354:2010 (lanyards), EN355:2002 absorber), EN362:2004 (connectors)
Materials:	Polyester/polyamide webbing. Steel and/or alloy.
Weight (kg):	
Industries:	All work at height industries.

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com

PDS1367

27/06/23